



- NOTES:**
1. PIPING MATERIAL: PE Carbon steel st. 304.
  2. CONNECTION TYPE: ANSI 150# FLANGE.
  3. MANUAL VALVES SHALL BE INSTALLED AT THE INLET AND OUTLET OF THE DISC FILTER.
  4. THE DRAIN PIPE SHALL BE CONNECTED TO THE DRAINAGE SYSTEM.
  5. POWER SUPPLY: 220V/1P/PHASE/50HZ.
  6. CONCRETE FOUNDATION (HEIGHT: 200MM)
  7. AND EXPANSION ANCHOR BOLTS ARE SUGGESTED FOR SITE INSTALLATION.

**Beijing Mide Technologies Co., Ltd**

| 标记 | 数量 | 分区 | 更改文件号 | 签名 | DATE | 审核 | 审核 | 审核 | 审核 | 审核 |
|----|----|----|-------|----|------|----|----|----|----|----|
| 1  | 1  |    |       |    |      |    |    |    |    |    |
| 2  | 1  |    |       |    |      |    |    |    |    |    |
| 3  | 1  |    |       |    |      |    |    |    |    |    |
| 4  | 1  |    |       |    |      |    |    |    |    |    |
| 5  | 1  |    |       |    |      |    |    |    |    |    |
| 6  | 1  |    |       |    |      |    |    |    |    |    |

MDG-12-8(10) DISCFIL/ITER/UNIT/ASSEMBLY QUANTITY NUMBER SCALE

MDG-12-00-01 / 1 1:1