



- NOTES:**
1. PIPING MATERIAL: PE Carbon steel st. 304.
 2. CONNECTION TYPE: ANSI 150# FLANGE.
 3. MANUAL VALVES SHALL BE INSTALLED AT THE INLET AND OUTLET OF THE DISC FILTER.
 4. THE DRAIN PIPE SHALL BE CONNECTED TO THE DRAINAGE SYSTEM.
 5. POWER SUPPLY: 220V/1PHASE/50HZ.
 6. CONCRETE FOUNDATION (HEIGHT: 200MM)
 7. AND EXPANSION ANCHOR BOLTS ARE SUGGESTED FOR SITE INSTALLATION.

<p style="text-align: center;">Beijing Mide Technologies Co., Ltd</p>		<p style="text-align: center;">MD3-4-4 DISINFILTRER</p>		<p style="text-align: center;">MATERIAL QUANTITY WEIGHT SCALE</p>	
<p>标记 数量</p>	<p>分区</p>	<p>更改文件号</p>	<p>签名</p>	<p>DATE</p>	<p>1</p>
<p>MD3-4-4</p>					<p>1</p>
<p>A</p>					<p>1:1</p>
<p>REV DESCRIPTION</p>	<p>REV</p>	<p>DATE</p>	<p>APP</p>	<p>DATE</p>	<p>DATE</p>
	4				
				<p style="text-align: center;">MD3-4-00-01</p>	
				<p style="text-align: center;">DATE</p>	